

UK Type Examination Certificate CML 21UKEX 21404X Issue 0**United Kingdom Conformity Assessment**

- 1 Product or Protective System Intended for use in Potentially Explosive Atmospheres UKSI 2016:1107 (as amended) – Schedule 3A, Part 1
- 2 Equipment **The explosion-proof wall clock type Ex-Time 40**
- 3 Manufacturer **Pepperl+Fuchs SE**
- 4 Address **Lilienthalstrasse 200
68307 Mannheim
Germany**

5 The equipment is specified in the description of this certificate and the documents to which it refers.

6 Eurofins E&E CML Limited, Newport Business Park, New Port Road, Ellesmere Port, CH65 4LZ, United Kingdom, Approved Body Number 2503, in accordance with Regulation 43 of the Equipment and Protective Systems Intended for Use in Potentially Explosive Atmospheres Regulations 2016, UKSI 2016:1107 (as amended), certifies that this equipment has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of equipment intended for use in potentially explosive atmospheres given in Schedule 1 of the Regulations.

The examination and test results are recorded in the confidential reports listed in Section 12.

7 If an 'X' suffix appears after the certificate number, it indicates that the equipment is subject to specific conditions of use (affecting correct installation or safe use). These are specified in Section 14.


8 This UK Type Examination certificate relates only to the design and construction of the specified equipment. Further requirements of the Regulations apply to the manufacturing process and supply of the product. These are not covered by this certificate.

9 Compliance with the Essential Health and Safety Requirements, with the exception of those listed in the confidential report, has been demonstrated through compliance with the following documents:

EN IEC 60079-0:2018

EN 60079-11:2012

10 The equipment shall be marked with the following:

 II 2 G

Ex ia IIC T4 Gb



CML 21UKEX21404X
Issue 0

11 Description

The explosion-proof wall clock type Ex-Time 40 is used within hazardous areas.
The permissible ambient temperature range is 0 °C to 50 °C.

Electrical data

Auxiliary energy Battery 1.5 V, type LR14

The following cells are suitable:

Manufacturer	Type
Varta	High Energy No. 4914
Varta	Industrial Alkaline No. 4014
Rayovac	Maximum Plus LR14
Duracell	Plus Alkaline MN 1400
Duracell	Procell Alkaline MN 1400
Panasonic	Powerline Industrial Alkaline LR14
Varta	Industrial PRO 4014 LR14
Panasonic	Powerline LR14AD*

*Marking on the battery shows only LR14

12 Certificate history and evaluation reports

Issue	Date	Associated report	Notes
0	16 Feb 2022	R14112CC/00	Prime Certificate issued.

Note: Drawings that describe the equipment are listed or referred to in the Annex.

13 Conditions of Manufacture

None.

14 Specific Conditions of Use

- Only the primary batteries specified in the Ex-Safety Manual may be used.
- The information required for installation and safe operation can be found in the Ex-Safety Manual

Certificate Annex

Certificate Number CML 21UKEX21404X
Equipment The explosion-proof wall clock type Ex-Time 40
Manufacturer Pepperl+Fuchs SE



The following documents describe the equipment defined in this certificate:

Issue 0

For drawings describing the equipment, refer to attached certificate PTB 02ATEX2197X. In addition to the drawings listed on PTB 02ATEX2197X, the following drawings include the additional marking required for this UK Type Examination certification:

Drawing No	Sheets	Rev	Approved date	Title
16-1555CM-10	1 to 2	0	16 Feb 2022	Additional Marking Requirements for UKCA